

Fango Stirrers RW / NFR

Medical Device Class I



Fango Stirrer RW 44, mounted on Heating Cabinet WS 14-6044 (Mounting example)

Intended Use

Type RW: Heating and tempering of fango paraffin in physiotherapy

Type NFR: Heating and tempering of natural fango in physiotherapy



Equipment

- Self-supporting housing made of stainless steel with structured surface
- Vessel RW made of aluminium, vessel NFR made of stainless steel
- Lid with two hinges and two gas springs
- Red, green or black handle bar
- Energy saving insulation
- Electronic temperature control with digital temperature display
- Safety thermometer, displays the temperature even when the device is switched off
- Indicator lamps for heating, stirring and high temperature treatment
- Interval stirring, continuous stirring
- Heated ball valve 1 ¼" for fango paraffin (RW)
- Ball valve 2" for natural fango (NFR)
- Motor protection relay

Technical Data

| Device Article Number | Filling Capacity (kg) | Heating Capacity (W) | Nominal Voltage (V) | Outer Dimensions L x D x H (mm) | Temperature Range |
|---------------------------------|---------------------------------|--------------------------------|-------------------------------|--|------------------------------|
| RW 44 E-Alu 0020.100 | 40 | 1000 | 230 | 540 x 582 x 620 | 30 °C - 110 °C 135 °C |
| RW 64 E-Alu 0022.100 | 60 | 1500 | 400 | 620 x 662 x 687 | 30 °C - 110 °C 135 °C |
| RW 84 E Alu 0024.100 | 80 | 2000 | 400 | 680 x 722 x 707 | 30 °C - 110 °C 135 °C |
| RW 104 E-Alu 0025.100 | 100 | 2500 | 400 | 730 x 772 x 702 | 30 °C - 110 °C 135 °C |
| NFR 64 E-VA 0022.300 | 60 | 2000 | 400 | 620 x 662 x 687 | Room temperature to 65 °C |
| NFR 84 E-VA 0024.300 | 80 | 2000 | 400 | 680 x 722 x 707 | Room temperature to 65 °C |
| NFR 104 E-VA 0025.300 | 100 | 2500 | 400 | 730 x 772 x 702 | Room temperature to 65 °C |